Framery



Video Conference Ready

Step into the soundproof world of video conferencing. The tilting screen bracket of O Video Conference Ready enables the attachment of various kinds of screens on the wall of the pod. You can fix a display or an all-in-one computer onto the screen bracket. The LED lighting surrounding the screen provides optimal lighting for video conferences. The control panel enables you to adjust the lighting and airflow.

framery

Framery O Video Conference Ready

Exterior

MATERIAL

EXTERIOR

Painted sheet metal or brushed stainless steel.

GLASS

Sound control laminated glass.

FRAME

Formica laminate on birch plywood with varnish trim.

EXTERIOR AND FRAME OPTIONAL COLORS



Interior

MATERIAL

SOLID WALLS AND ROOF

Sandwich element of sheet metal, birch plywood, recycled acoustic foam and acoustic felt. Anti-static and stain resistant low loop pile carpet for public spaces.

TABLE

Formica white laminate on birch plywood with varnish trim.







CONTROL PANEL

The control panel enables you to adjust:

The brightness of the new improved ceiling light

The light surrounding the screen

The capacity of the airflow

Technical specifications

MEASUREMENTS

SIZE: 221 cm x 100 cm x 100 cm (h, w, d) (87 in x 40 in x 40 in)

INTERIOR SIZE: 200 cm x 80 cm x 95 cm (78 in x 31.5 in x 37.4 in)

DOOR: Left handed, minimum clear opening width 78.5 cm (30.9 in)

TABLE SIZE: 75 cm x 30 cm x 12 cm (w, d, h) (29.5 in x 11.8 in x 4.7 in)

TABLE HEIGHT: 102,5 cm (40 in)

STOOL: 68,5 - 81,5 cm (26.8 - 31.9 in)

WEIGHT: 350 kg / 772 lb

ADDITIONAL INFO

TABLE

White wide table with cable feed from monitor. Power socket + USB (Pixel TUF)

SCREEN BRACKET

Screen not included.

Screen specifications: Maximum size 24" with flat VESA 100 x 100 mounting surface.

CERTIFICATES







Design your own pod at: configurator.frameryacoustics.com